

Related Products and Services

- ▶ **Omni-ID Dura 1500** - Long range, high durability RFID tag product for heavy industry applications involving metal.
- ▶ **Omni-ID Exo 750**- Extreme durability, long range and global operability in a small, square footprint, on metal RFID tag.
- ▶ **Omni-ID IQ 800P**- Large premium label for plastic assets.
- ▶ **Service Bureau** - Omni-ID offers a full service bureau for printing and pre-encoding Omni-ID tags at point of manufacture.



Environmental Specifications

Operating Temperature	ABS: -40 to +65 °C PC: -40 to +100 °C
Long term Max Temperature ¹ exposure - (days,weeks,years)	ABS: +65 °C PC: +100 °C
Short term Max Temperature ¹ exposure - (minutes,hours)	ABS: +75 °C PC: +120 °C
IP Rating	IP68
Shock and Vibration	MIL STD 810-G
Impact	>25kg from 1m
Attachment	Manual (standard) Standard foam adhesive (option) Premium foam adhesive (option)
Certifications	RoHS approved CE approved ATEX/IECEX certified (option) US&Canada (C1D1/D2) certified (option)
Warranty	3 years

1. Excludes adhesive options, consult adhesive data sheets for recommended temperature ratings.
2. Testing methodology available on request

Ordering Information

Order Numbers	009 - GS :302 (PC encasement) :304 (ATEX/IECEX certified) :307 (US&Canada (C1D1/D2) certified) :507 (std. foam), :508 (premium foam) :701 (Standard Service Bureau) :702 (Custom Service Bureau)
---------------	---



Omni-ID office locations: US | UK | China | India | Germany
For product or technology inquiries email: sales@omni-id.com