



## Omni-ID Flex™ (European Version)

Omni-ID Flex is a medium-range passive UHF RFID tag with a managed read range greater than 3.5 metres—offering increased visibility of assets and stock/intermediates, and greater efficiency in manufacturing and retail environments. The product delivers an outstanding performance-to-size ratio, while providing balanced on/off metal performance. These features are critical in the area of laptop tracking, where Omni-ID Flex ensures accurate asset registration and security benefits.

Omni-ID Flex comes as standard with a printed label finish. It is also available in a low-profile ruggedized rigid case for applications with harsh environmental requirements.

### Barcodes meet RFID.

In order to provide a transition between barcode and RFID functionality, Omni-ID Services are available to print barcode and human readable information on the outer label, and add chip programming with the associated EPC code on each individual tag.

## Omni-ID is RFID, redefined.

We eliminated the interference from metals and liquids that cause conventional RFID tags to underperform in harsh environments. Our breakthrough technology enables you to track high value assets and manage supply chains with near perfect accuracy. Yet, not only have we developed the industry's most reliable RFID tags, we've also built alliances with the most trusted providers of RFID hardware, software, and solutions. Together, we can ensure that you have a complete solution that meets your unique requirements. All of which explains why a growing number of companies are choosing to identify with Omni-ID. Interested in joining them? [Contact Omni-ID today.](#)

UHF "On Metal" Tag Comparison					
	Omni-ID Tag	Stand-off/Spacer Tag	Magnetic Isolating Barrier Tag	Tuned Antenna and Ground Plane Tags	Patch Antenna Tags
Size and shape	Small	Large	Small	Medium	Small
Balanced performance on and off metal	High	Medium	Low	Medium	Low
Reliability/robust performance in a metal environment	High	Low	Low	Low	High
Value for money	High	Medium	Low	Medium	Low

### Omni-ID Flex Applications

- Laptop tracking
- Shelf-edge retail and warehouse location
- Automotive parts and components tracking
- Tool tracking

### Omni-ID Flex Highlights

- Ultimate reliability and accuracy on any material in any environment
- Increased visibility of assets and conveyances
- Improved efficiency in locating or auditing items
- 240 bit EPCglobal Class-1 Gen2-compliant silicon
- Over 3.5m (11 ft) maximum read range (on metal) under European standards
- Supplied with label finish or optional ruggedized rigid case
- Footprint 77mm x 15mm x 2.5mm when supplied with label finish
- Footprint 97mm x 21mm x 5.7mm when supplied in a ruggedized rigid case

### Contact Omni-ID

For more information, please contact:  
 Email [customer.services@omni-id.com](mailto:customer.services@omni-id.com)  
 Call +44 (0)1252 416 487 or 650-587-0812

Visit [www.omni-id.com](http://www.omni-id.com) to learn more about Omni-ID's complete line of RFID products

#### European Office

The Enterprise Centre  
 Coxbridge Business Park  
 Alton Road, Farnham, Surrey  
 GU10 5EH, United Kingdom  
 Tel: +44 (0)1252 748020  
 Fax: +44 (0)1252 748021

#### U.S. Office

1065 East Hillsdale Boulevard, Suite 400  
 Foster City, CA 94404  
 Tel: 650-571-OMNI (6664)  
 Fax: 650-571-6624

1 Quoted performance achieved using standard Omni-ID test methodology, details available upon request.

2 Product designed to meet IP68 (please contact Omni-ID for further details).

3 Temperature testing methodology in accordance with BS EN 60068-2-1 and BS EN 60068-2-2.

### Omni-ID Flex Specifications

Omni-ID Flex (European Version)		
<b>General Information</b>		
Frequency range	865.6MHz to 867.6MHz	
IC	Alien Higgs H2	
<b>RF Specifications</b>		
IC Protocol	UHF EPC Class-1 Gen2	
IC Memory	240 bits	
Read range on metal <sup>1</sup>	>3.5m	
Read range off metal <sup>1</sup>	>3.5m	
<b>Physical Specifications</b>		
Encasement	<b>Label covering</b>	<b>Ruggedized rigid case</b>
Attachment	3M 9472LE self adhesive	2x Ø 5mm rivet hole and 3M 9472LE self adhesive
Length	77mm	97mm
Width	15mm	21mm
Thickness	2.5mm	5.7mm
Casing material	Laminated label	ABS
Colour	N/A	Light Blue
Mass	2.6g	11.7g
Ingress protection	N/A	IP68 <sup>2</sup>
Operating temperature <sup>3</sup>	-20°C to +65°C	-20°C to +65°C
Order reference number	0112-0203-0405	0112-0203-0207