






# IQ Range – Labels

## FEATURED COMPARISON GUIDE

Product Name		 IQ 150	 IQ 350	 IQ 400P	 IQ 600	 IQ 800P
Typical Applications		IT, office, hospital asset tracking Weapons, pipes, road signs Warehouse management	IT and office asset tracking Logistics with metallic packaging Intermodal logistics	Plastic facias's on IT equipment Identification of IT & office hardware	Logistics- metal produce & packaging Pipe manufacturing & recertification IT, Office, & Hospital tracking	Plastic RTI's and containers Plastic pallets
RF Specifications	Frequency Range (MHz)	902-928 (US) 866-868 (EU)	902-928 (US) 866-868 (EU)	860-960 (GS)	902-928 (US) 866-868 (EU)	860-960 (GS)
	Read Range (m) - Fixed reader	Up to 1.6	Up to 3.5	Up to 5.0	Up to 6.0	Up to 10.0
	Read Range (m) - Handheld reader	Up to 1.0	Up to 2.0	Up to 2.5	Up to 3.0	Up to 5.0
	Material Compatibility	Optimized for all materials	Optimized for all materials	Plastic and non-metal substrates	Optimized for all materials	Plastic and non-metallic substrates
	IC Type	Impinj Monza R6-P	Impinj Monza R6-P	Alien Higgs 3	Impinj Monza R6-P	Alien Higgs 3
Physical and Environmental Specifications	Encasement / Material	Synthetic label	Synthetic label	Synthetic label	Synthetic label	Synthetic label
	Size (mm)	55.0 × 12.5 × 1.20	50.0 × 12.5 × 1.30	46.5 × 12.4 × 0.24	96.0 × 24.0 × 1.30	95.0 × 21.0 × 0.24
	Weight (g)	0.44	0.50	0.15	1.50	0.65
	Operating Temperature (°C)	-40 to +85	-40 to +85	-40 to +85	-40 to +85	-40 to +85
	Ingress Protection	IP68	IP68	IP68	IP68	IP68
	Shock and Vibration	MIL STD 810-G	MIL STD 810-G	MIL STD 810-G	MIL STD 810-G	MIL STD 810-G
	Attachment	Self Adhesive (std)	Self Adhesive (std)	Self Adhesive (std)	Self Adhesive (std)	Self Adhesive (std)
Order Codes†	125 – US, EU	158 – EU, US	055 – GS	133 – US, EU	056 – GS	

†Order option codes are listed on the datasheets.