



Omni-ID Prox™ (European Version)

Omni-ID Prox offers the smallest form factor and best performance of any UHF RFID tag on the market today. This short-range passive RFID tag has a managed read range greater than 1.5 metres. It is ideally suited for IT asset identification, where increased visibility and asset registration are essential. As such, Omni-ID Prox delivers unmatched precision for the tracking of smaller high-value assets, electronic devices, communications/network cards, servers, and other assets or applications that demand high performance. What's more, the tag's compact form factor and extremely small footprint make it a discrete solution for items with little available real estate.

Omni-ID Prox comes as standard with a printed label finish. It is also available in a low-profile ruggedized rigid case for applications with harsh environmental requirements.

Barcodes meet RFID.

In order to provide a transition between barcode and RFID functionality, Omni-ID Services are available to print barcode and human readable information on the outer label, and add chip programming with the associated EPC code on each individual tag.

Omni-ID is RFID, redefined.

We eliminated the interference from metals and liquids that cause conventional RFID tags to underperform in harsh environments. Our breakthrough technology enables you to track high value assets and manage supply chains with near perfect accuracy. Yet, not only have we developed the industry's most reliable RFID tags, we've also built alliances with the most trusted providers of RFID hardware, software, and solutions. Together, we can ensure that you have a complete solution that meets your unique requirements. All of which explains why a growing number of companies are choosing to identify with Omni-ID. Interested in joining them? [Contact Omni-ID today.](#)

UHF "On Metal" Tag Comparison					
	Omni-ID Tag	Stand-off/Spacer Tag	Magnetic Isolating Barrier Tag	Tuned Antenna and Ground Plane Tags	Patch Antenna Tags
Size and shape	Small	Large	Small	Medium	Small
Balanced performance on and off metal	High	Medium	Low	Medium	Low
Reliability/robust performance in a metal environment	High	Low	Low	Low	High
Value for money	High	Medium	Low	Medium	Low

Omni-ID Prox Applications

- IT asset identification
- Product tracking during manufacturing
- Tool tracking
- Asset rentals

Omni-ID Prox Highlights

- Ultimate reliability and accuracy on any material in any environment
- Increased visibility of assets and conveyances
- Improved efficiency in locating or auditing items
- Very small form factor
- 240 bit EPCglobal Class-1 Gen2-compliant silicon
- Over 1.5m (5 ft) maximum read range (on metal) under European standards
- Supplied with label finish or optional ruggedized rigid case
- Footprint 35mm x 10mm x 4mm when supplied with label finish
- Footprint 55mm x 16mm x 7.5mm when supplied in a ruggedized rigid case

Contact Omni-ID

For more information, please contact:

Email customer.services@omni-id.com

Call +44 (0)1252 416 487 or 650-587-0812

Visit www.omni-id.com to learn more about

Omni-ID's complete line of RFID products

European Office

The Enterprise Centre
Coxbridge Business Park
Alton Road, Farnham, Surrey
GU10 5EH, United Kingdom
Tel: +44 (0)1252 748020
Fax: +44 (0)1252 748021

U.S. Office

1065 East Hillsdale Boulevard, Suite 400
Foster City, CA 94404
Tel: 650-571-OMNI (6664)
Fax: 650-571-6624

1 Quoted performance achieved using standard Omni-ID test methodology, details available upon request.

2 Product designed to meet IP68 (please contact Omni-ID for further details).

3 Temperature testing methodology in accordance with BS EN 60068-2-1 and BS EN 60068-2-2.

Omni-ID Prox Specifications

Omni-ID Prox (European Version)		
General Information		
Frequency range	865.6MHz to 867.6MHz	
IC	Alien Higgs H2	
RF Specifications		
IC Protocol	UHF EPC Class-1 Gen2	
IC Memory	240 bits	
Read range on metal ¹	>1.5m	
Read range off metal ¹	>1.0m	
Physical Specifications		
Encasement	Label covering	Ruggedized rigid case
Attachment	3M 9472LE self adhesive	1x Ø 5mm rivet hole and 3M 9472LE self adhesive
Length	35mm	55mm
Width	10mm	16mm
Thickness	4mm	7.5mm
Casing material	Laminated label	ABS
Colour	N/A	Light Blue
Mass	1.3g	3.8g
Ingress protection	N/A	IP68 ²
Operating temperature ³	-20°C to +65°C	-20°C to +65°C
Order reference number	0113-0203-0405	0113-0203-0207