



View Range – Display Tags

FEATURED COMPARISON GUIDE

Product Name	 View 3	 View 4
Typical Applications	Manufacturing: Replenishment, Work instructions & Container management Health Care: Equipment Tracking and Directional labeling IT: Asset Tracking and status Logistics: Container Management, Sortation/Postal, Warehousing/Yard Management, Food Supply Chain	Manufacturing: Replenishment, Work instructions & Container management Health Care: Equipment Tracking and Directional labeling IT: Asset Tracking and status Logistics: Container Management, Sortation/Postal, Warehousing/Yard Management, Food Supply Chain
Screen	Electrophoretic e-paper display Full graphic (black & white), 120° viewing angle (in sunlight)	Electrophoretic e-paper display Full graphic (black & white), 120° viewing angle (in sunlight)
Size (mm) (in)	146.5 × 50 × 14.1 5.77 × 1.97 × 0.56	148.5 × 102.5 × 13.9 5.85 × 4.04 × 0.55
Diagonal Viewable Area (in)	2.9	4.2
User Memory	16 image pages	16 image pages
Battery life ¹	Up to 4 yrs	Up to 4 yrs
Passive Read Range: ² Passive Write Range	Up to 5m on and off metal Up to 3m on and off metal	Up to 5m on and off metal Up to 3m on and off metal
Active Read & Write Range	80m on metal 100m off metal	80m on metal 100m off metal
IC Type (chip)	MonzaX-2K	MonzaX-2K
Ingress Protection ³	IP65	IP65
Operating Temperature (°C)	0 to +40 °C	0 to +40°C
Attachment	Adhesive, Bracket, or Zip tie	Adhesive, Bracket, or Zip tie
Order Codes ⁴	OMNI-V3-G2-ACCY (US, EU) OMNI-V3-G2-ACCY-SB (US,EU)	OMNI-V4-G2-ACCY (Global) OMNI-V4-G2-ACCY-SB (Global)

¹ Actual battery life could be greater depending on configuration and use.

² Indoor installation typical power settings shown. Optimal environments can significantly enhance performance.

³ Rating does not apply with blue silicone buttons

⁴ Order Option Codes are listed on the datasheets